



16	BLK
15	BLA
14	DB7
13	DB6
12	DB5
11	DB4
10	DB3
9	DB2
8	DB1
7	DB0
6	□
5	W
4	S
3	V
2	VDD
1	GND

SPECIFICATION:

- 1). Driving: DUTY:1/16, BIAS:1/5, VLCD:4.5V, VDD:5.0V
- 2). Viewing angle: 6 0'CLOCK
- 3). Display mode: STN(YELLOW-GREEN),POSITIVE,TRANSPARENT
- 4). Operating temp: 0°C~+50°C
- 5). Storage temp: -10°C~+60°C
- 6). Controller IC: SPLC780D1 (or compatible)
- 7). Backlight: Edge(YG), VLED=5.0V
- 8). Dimensions with mark "*" are important, with mark "()" are referenced
- 9). All the raw materials are RoHS compliant



深圳市三元晶科技有限公司
ShenZhen TCC LCD Hi-Tech Co., Ltd.

REV	REVISION RECORD	DATE	MODEL NO.	GENERAL TOL:
A	First issue		B1604CV10-5C10YL5-B5NG	± 0.3
B			模组型号	
C			APPROVED BY 审核	
D			CHECKED BY 检查	
			DRAWING BY 绘图	
			Luoxian	
			2012/07/11	
			PROJECTION 三角法	
			UNIT: mm	