



Specification:

- 1). Driving: Duty:1/64, Bias:1/9, VLCD:1.3.2V(Ref), VDD:5.0V
- 2). Viewing Direction: 6 O'clock
- 3). Display mode: STN/Positive/Transflective/Y-G
- 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 5). IC: SBN0064G / SBN6400G
- 6). Backlight: LED,White/YG
- 7). Dimensions with mark "*" are important, with mark "(")" are referenced
- 8). All the raw materials are RoHS compliant

PIN	1	2	3	4	5	6	7	8	9	10
CONNECTION	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3
PIN	11	12	13	14	15	16	17	18	19	20
CONNECTION	DB4	DB5	DB6	DB7	/CS1	/CS2	/CS3	/RST	VOUT	BLA

REV	REVISION RECORD	DATE	MODEL NO.		DRAWING BY		GENERAL TOL: ± 0.3	
A0	First issue	11-2/11	SYB19264D1V10		Jequil		未注公差	
			APPROVED BY		CHECKED BY		PAGE: 1 OF 1	
			模 组 型 号		DRAWING BY		页 面	
			TCC		Jequil		UNIT: mm	
			深圳市三元晶液晶显示科技有限公司		PROJECTION		三 角 法	
			ShenZhen TCC LCD Hi-Tech Co., Ltd.		UNIT: mm		单 位	